

## **Tungsten Cemented Carbide Blade Sharp Cutting Edge For Chemical Fiber Cutting**



### **Items Common sizes L\* W \* T(mm)**

- 1 193\*18.9\*0.884
- 2 170\*19\*0.884
- 3 140\*19\*1.4
- 4 140\*19\*0.884
- 5 135.5\*19.05\*1.4
- 6 135\*19.05\*1.4
- 7 135\*18.5\*1.4
- 8 118\*19\*1.5

9 117.5\*15.5\*0.9

10 115.3\*18.54\*0.84

11 95\*19\*0.884

12 90\*10\*0.9

Acceptable for customer's design

**Production description of carbide fiber cutting blade**

Grade	Density	T.R.S	Hardness	characteristics and Application
	g/cm <sup>3</sup>	≥ N/mm <sup>2</sup>	HRA	
MR020	14.35-14.5	3000	91.8	Sub-micron grain,apply to cutting corrugated board,chemical fiber,plastics,leather,battery pole pieces,all kinds of milling cutters and hole-machining tools
MR030	13.95-14.1	3200	90.5	Sub-micron grain,superb abrasive resistance and toughness,apply to woodworking cutters,cutting corrugated board,battery pole pieces etc
MR040	13.8-13.95	3200	89.8	Sub-micron grain,superb abrasive resistance and toughness , apply to woodworking cutters, rolling shear blades, suitable for cutting paperboard

