

# STANDARD FEATURES

## MECHANICAL

90,000-mile spark plug interval <sup>1</sup>
4-wheel Anti-Lock Brake System (ABS) with front and rear disc brakes
Battery saver automatically deactivates interior lights
Body-on-frame construction
Power rack-and-pinion steering
Suspension – Front: independent short- and long-arm with stabilizer bar, coil spring (4x2 XL and XLT) or torsion bar (4x4 and 4x2 SPORT); rear: 2-stage leaf springs

## SEATING

Front 60/40 split seat (XL and XLT)
Cloth bucket seats (SPORT)

## INTERIOR

Air conditioning
Cargo net (rear passenger; SuperCab only)
Cupholders
Dome light
Glove compartment
Grab handles for driver and front passenger
Powerpoint (12v)
Rally gauge cluster with tachometer

## EXTERIOR

6-ft. pickup box
Cargo box tie-downs hooks (4)
H-bar-style grille
Raised power dome hood
Solar-tinted glass
Stone guards/mud flaps (vary by model)
Tailgate with quick release
Windshield wipers – Intermittent

## SAFETY & SECURITY

Personal Safety System™ for driver and right-front passenger includes dual-stage front airbags <sup>2</sup> ; safety belt pretensioners, safety belt energy-management retractors, safety belt usage sensors, driver's seat position sensor, crash severity sensor, restraint control module and Front-Passenger Sensing System
AdvanceTrac® with RSC® (Roll Stability Control™)
Belt-Minder® front safety belt reminder
Front-seat side airbags <sup>2</sup>
Safety belt height adjusters for front-outboard positions
SecuriLock® Passive Anti-Theft System
Side-intrusion door beams
Tire Pressure Monitoring System (excludes spare)

<sup>1</sup>Under normal driving conditions with routine fluid and filter changes.

<sup>2</sup>Always wear your safety belt and follow airbag warning label instructions.

## ENGINES

<b>2.3L DOHC I-4</b>	
Horsepower	143 @ 5,250 rpm
Torque (lb.-ft.)	154 @ 3,750 rpm
<b>4.0L V6</b>	
Horsepower	207 @ 5,250 rpm
Torque (lb.-ft.)	238 @ 3,000 rpm

## EPA-ESTIMATED FUEL ECONOMY

<b>2.3L DOHC I-4 (4x2)</b>	
Manual transmission	22 mpg city/27 hwy
Automatic transmission	19 mpg city/24 hwy
<b>4.0L V6 (4x2)</b>	
Manual transmission	16 mpg city/21 hwy
Automatic transmission	15 mpg city/20 hwy
<b>4.0L V6 (4x4)</b>	
Manual transmission	15 mpg city/19 hwy
Automatic transmission	14 mpg city/18 hwy

## MAXIMUM LOADED TRAILER WEIGHT<sup>3</sup> (LBS.)

	Axle Ratio	GCWR	Regular Cab 4x2	SuperCab <sup>3</sup> 4x2/4x4
<b>2.3L DOHC I-4</b>				
Manual transmission	3.73 or 4.10	4,800	1,500	1,340/ —
Automatic transmission	4.10	5,500	2,160	2,000/ —
<b>4.0L V6</b>				
Manual transmission	3.55	7,000	—	3,340/ —
Automatic transmission	3.55	9,500	—	5,800/ —
Manual transmission	3.73 or 4.10	7,000	—	— /3,100
Automatic transmission	3.73 or 4.10	9,500	—	— /5,560

## MAXIMUM PAYLOAD<sup>4</sup> (LBS.)

	Box Size	Max. GVWR	Max. Available Payload
<b>2.3L DOHC I-4</b>			
Regular Cab 4x2	6'	4,300	1,130
SuperCab 4x2 <sup>3</sup>	6'	4,760	1,420
<b>4.0L V6</b>			
SuperCab 4x2	6'	4,760	1,220
SuperCab 4x4 <sup>3</sup>	6'	5,150	1,370
<b>4.0L V6<sup>5</sup></b>			
SuperCab 4x2	6'	5,100	1,560
SuperCab 4x4 <sup>3</sup>	6'	5,280	1,500

## DIMENSIONS & CAPACITIES

	Regular Cab 4x2	SuperCab 4x2/4x4
<b>Exterior</b>		
Overall length	189.4"	203.6"
Wheelbase	111.5"	125.7"/125.9"
Overhang – Front	34.0"	34.0"
Overhang – Rear	44.0"	44.0"/43.8"
Width – Excluding mirrors	69.3"	69.4"/71.3"
Width – Including mirrors	81.3"	81.3"
Height	66.2"	66.3"/67.7"
Ground clearance	8.9"	8.6"/8.2"
Loadfloor height	29.7"	29.5"/31.9"
Ramp breakover angle	24.4°	23.3°/18.6°
Angle of approach	23.5°	23.8°/24.9°
Angle of departure	24.6°	24.3°/27.4°
Fuel capacity (gal.)	17.0	19.5

## Interior

	Regular Cab 4x2	SuperCab 4x2/4x4
<b>Front</b>		
Head room	39.2"	39.2"
Shoulder room	54.5"	54.5"
Hip room	52.7"	52.7"
Leg room	42.4"	42.4"
Passenger volume (cu. ft.)	52.5	63.0
<b>Rear</b>		
Head room	—	33.2"
Shoulder room	—	14.1"
Hip room	—	18.7"
Leg room	—	39.1"
Passenger volume (cu. ft.)	—	10.6
Luggage capacity behind front row (cu. ft.)	—	25.3

## 6' Cargo Box

	Regular Cab 4x2	SuperCab 4x2/4x4
Volume (cu. ft.)	37.4	37.4
Inside height	16.5"	16.5"
Length at floor	72.7"	72.7"
Width at wheelhouse	40.5"	40.5"
Maximum width at floor	54.4"	54.4"

Cargo and load capacity limited by weight and weight distribution.

<sup>3</sup>Maximum capabilities shown are for properly equipped vehicles with required equipment and a 150-lb. driver. Weight of additional options, equipment, passengers and cargo must be deducted from this weight. For additional information, see your Ford Dealer. NOTE: Ranger does not have an electric brake wiring provision. Certain states require electric trailer brakes over a specified trailer weight. In those states, the Ranger maximum loaded trailer weight is limited to the state regulation. Check your state's trailer weight regulations. SuperCab 2-door model numbers given. <sup>4</sup>Maximum capabilities shown are for properly equipped vehicles with required equipment. Weight of additional options, equipment, passengers and cargo must be deducted from this weight. For additional information, see your Ford Dealer. <sup>5</sup>With Payload Package #2.

# 2011 RANGER

ford.com

